



Description

This USB 2.0 A-B cable is made according to the UL2725 standard, with double shielding (foil+braid) for stable and safe data transmission. It has nickel-plated connectors and PVC protection, which ensures a long service life and resistance to interference. It is intended for connecting printers, scanners and other USB devices.

Specification

- Cable type: USB 2.0 A (male) - USB 2.0 B (male)
- Model / P/N: 1487596-X
- Length (L):
 - 3000 mm (3 m)
 - 2000 mm (2 m)
 - 1000 mm
 - 1500 mm
 - or at the customer's request

Cable construction

- *Cable (wire):*
 - Model: UL2725 (USB 2.0 Cable)
 - Structure: 1 pair + 28AWG/24AWG
 - Armor: aluminum foil + braided wire (AL + D + B)
 - Outer diameter: 4.5 mm
 - Color: black

Connectors:

- USB A (AM) - nickel-plated housing (3-part construction)
- USB B (BM) - nickel-plated housing (3-part construction)

Case material:

- PVC 45P, black color

Aarmor:

- Copper foil (thickness 0.65 mm, width 8 mm, length 15 mm)



• **Connecting Pins (Wires)**

Pin	Color	Connection
1.	Red	1 → 1
2.	White	2 → 2
3.	Green	3 → 3
4.	Black	4 → 4

Shell Armor (drainage + braid) Shell

• **Electrical characteristics**

- Open and short circuit test: 100% tested
- Contact resistance: max 2 Ω
- Insulation resistance: min 10 M Ω
- Hi-Pot test: DC 630V / 10 ms

• **Additionally**

Label (sticker):

- Dimensions: 25 × 13 mm (white)
- Text: STS Taliija DOO + "Made in China"